

INSULATE  
SEAL  
PROTECT

## PIPE WRAP TAPE

A CORROSION PROTECTION, PRESSURE SENSITIVE VINYL TAPE GIVING COMPLETE ENVIRONMENTAL, MECHANICAL AND ELECTRICAL PROTECTION FOR ALL TYPES OF PIPEWRAPPING APPLICATIONS. UV, BACTERIA AND FUNGUS RESISTANT. CET50 TAPE CAN BE USED FOR BOTH OVERHEAD AND DIRECT BURIAL APPLICATIONS.

## FEATURES AND BENEFITS

- 10 mil thickness
- Abrasion resistant
- Bacteria & fungus resistant
- Highly resistant to sun, water, oil, acids, alkalis, corrosive chemicals
- Lead free

## STANDARDS

- Federal Specification L-T-1512A

## TYPICAL APPLICATIONS

- Protect pipes, pipe joints, conduit and couplings in overhead or direct burial applications
- Corrosion protection



# PIPE WRAP TAPE

# CET50

## DIMENSIONS

ORDER NUMBER	COLOR	THICKNESS		WIDTH		LENGTH	
		MM	IN	MM	IN	M	FT
CET50	Black	0.254	0.010	51	2	30	100

\* Additional sizes available upon request

## TECHNICAL DATA

PROPERTY	TEST METHOD	TYPICAL PERFORMANCE	UNITS
<b>PHYSICAL</b>			
Tensile Strength	ASTM D 1000	25 (44)	lb/in (N/cm)
Elongation	ASTM D 1000	250	%
Adhesion			
	To Steel	ASTM D 1000	22 (2.42)
	To Backing	ASTM D 1000	18 (1.98)
			oz/in (N/cm)
			oz/in (N/cm)
<b>ELECTRICAL</b>			
Dielectric Strength	ASTM D 1000	1000 (40)	V/mil (kV/mm)
Dielectric Constant	ASTM D 150	3.2	
Power Factor	ASTM D 150	0.07	
Insulation Resistance	ASTM D 1000	1x10 <sup>6</sup>	MΩ

## ORDERING

- Please specify the product name/order reference number. Order Example: CET 50

## STORAGE

- Store the product in its original packaging in a clean dry place and placed in a horizontal position under cover in temperature conditions between 5°C to 35°C (41°F to 95°F).
- Stock rotation is recommended.